

COMPRESSOR LUBRICANT CL 1500 PHLA-3

Date of issue: 01.12.2010

Sonneborn Refined Products B.V. urges the recipient of this Safety Data Sheet to study it carefully to become aware of hazards, if any, of the product involved. In the interest of safety you should (1) notify your employees, agents and contractors of the information on this sheet,(2) furnish a copy to each of your customers for the product, and (3) request your customers to inform their employees and customers as well.

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Identification of the substance or preparation

Compressor Lubricant

Use of substance/preparation:

Compressor Lubricants are a family of high performance lubricants that consist of white mineral oil, viscosity improvers and lubricity packages. The oils are designed to lubricate under extreme conditions of pressure, temperature and in the presence of supercritical ethylene gas.

Company identification

Sonneborn Refined Products B.V.
Mainhavenweg 6
1043 AL Amsterdam
The Netherlands
Tel: +31-20-6117475
Fax: +31-20-6111170
E-mail: QEHS@sonneborn.com

Emergency telephone number

Tel.: +31.20.611.74.75

2. HAZARDS IDENTIFICATION

EC/GHS Classification : Not classified as dangerous under EC/GHS-criteria
Human Health Hazards : None
Physico-chemical and environmental hazards and effects: None

3. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT	% BY WEIGHT	HAZARD	DANGER SYMBOL(S)
No hazardous components			

4. FIRST AID MEASURES

Swallowing

Do not induce vomiting. Obtain medical attention immediately.

Inhalation

No emergency care anticipated.

COMPRESSOR LUBRICANT CL 1500 PHLA-3

Skin contact

No emergency care anticipated.

Eye contact

Flush eyes thoroughly with water for several minutes. Obtain medical attention if discomfort persists.

Notes to physician

None

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable : Extinguish with:

- dry chemical
- carbon dioxide (in case of small fires)
- water fog
- foam
- sand or earth

Unsuitable : Do not use water jet.

Special fire fighting procedures

Do not direct a solid stream of water or foam into burning material; this may cause spattering and spread the fire.

Special protective equipment for firefighters

Self-contained breathing apparatus.

Unusual fire and explosion hazards

Following products may be produced during a fire: Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Wear suitable protective equipment.

Environmental precautions

Avoid runoff to sewers or waterways. Dike area of spill to prevent spreading and pump liquid to salvage tank. Waste: avoid washing into watercourses. Use methods consistent with local regulations or incinerate.

Methods for cleaning up

Dike to contain spill. Absorb on inert material such as sand, earth, vermiculite. Stop the leak if it can be done without risk.

7. HANDLING AND STORAGE

HANDLING

Do not handle at temperatures $> +60\text{ }^{\circ}\text{C}$

Ventilation

General (mechanical) room ventilation is expected to be satisfactory for use at room temperature.

STORAGE**Storage requirements**

Keep away from heat, sparks and flame. Do not store at temperatures: $> 25\text{ }^{\circ}\text{C}$

Store protected from light

COMPRESSOR LUBRICANT CL 1500 PHLA-3

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMIT VALUES

COMPONENT	COUNTRY	TYPE REMARK	VALUE
Mineral Oil Mist		If used in way that generates a "mist" observe the limits for Mineral Oil Mist. TWA (mist), ACGIH STEL (mist), ACGIH	5 mg/m3 10 mg/m3

OCCUPATIONAL EXPOSURE CONTROLS

Respiratory protection

None expected to be needed.

If used in a way that generates a "mist": wear an appropriate respirator

Hand protection / protective gloves

Wear gloves impervious to this material

Eye protection

Safety glasses.

Faceshield

Skin protection

Minimise all forms of skin contact

Environmental Exposure Controls:

Store in a second containment to catch leakages

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	:	Liquid
Color	:	Colorless
Odor	:	None

Important health, safety and environmental information

Flash point	:	> 220 °C Method: ASTM D92
Upper explosion limits	:	Not determined
Lower explosion limits	:	Not determined
Vapor pressure	:	< 0,1 hPa at 20 °C
Density	:	0,86 - 0,89 g/cm3 at 20 °C

COMPRESSOR LUBRICANT CL 1500 PHLA-3

Bulk density	:	Not available
Solubility in water	:	Negligible
Kinematic viscosity	:	275-295 mm ² /s at 40 °C – ASTM D 445

Other information

Melting point	:	Not applicable
Autoignition temperature	:	Not determined

10. STABILITY AND REACTIVITY

STABILITY

Stable.

Conditions to avoid

Extremes of temperature and direct sunlight

Materials to avoid

Strong oxidizing agents.

Hazardous decomposition products

No hazardous decomposition products to be formed during normal storage

Combustion may produce carbon monoxide and/or carbon dioxide.

11. TOXICOLOGICAL INFORMATION

GENERAL

No evidence of harmful effects from available information.

12. ECOLOGICAL INFORMATION

White mineral oil will be inherently biodegradable in water under aerobic conditions, and will be ultimately biodegrades by micro-organisms (although the biodegradability of White Mineral Oil will necessarily be limited by its low solubility in water).

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations or incinerate.

COMPRESSOR LUBRICANT CL 1500 PHLA-3

14. TRANSPORT INFORMATION

ADR/RID

This product is not regulated by ADR.

IMDG

This product is not regulated by IMDG.

ICAO

This product is not regulated by ICAO.

15. REGULATORY INFORMATION

EC/GHS classification

According to EC/GHS-regulations this product is not classified or labelled.

Chemical Inventory

Europe : This product is on the EINECS inventory.

16. OTHER INFORMATION

Recommended uses and restrictions

Please consult the product and/or application information bulletins for this product.

Further information

Where appropriate, use CE approved personal protection equipment.

|| A vertical line in the left margin of the report indicates a change compared to the previous version.

This Safety Data Sheet conforms to EC Directive 1907/2006 and amendments.

The opinions expressed herein are those of qualified experts within Sonneborn Refined Products B.V.. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and of these opinions and the conditions of use of this product are not within the control of Sonneborn Refined Products B.V., it is the user's obligation to determine the conditions of safe use of the products.