

WITCOVAR 146

Date of issue: 25.07.2005

Sonneborn Refined Products B.V. urges the recipient of this Safety Data Sheet to study it carefully to become aware of hazards, if any, of the product involved. In the interest of safety you should (1) notify your employees, agents and contractors of the information on this sheet,(2) furnish a copy to each of your customers for the product, and (3) request your customers to inform their employees and customers as well.

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING**Identification of the substance or preparation**

Chemical name : Wax

Company identification

Sonneborn Refined Products B.V.
Spaarndamseweg 466
NL - 2022 EB Haarlem
Tel: +31-75-6283854
Fax: +31-75-6210811

Emergency telephone number

Tel.: +31.20.611.74.75

Environmental, Health and Safety Department

Sonneborn Refined Products B.V.
Mainhavenweg 6
1043 AL Amsterdam
The Netherlands
Tel.: +31.20.611.74.75
Fax: +31.20.611.09.59

2. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT/CAS#	% BY WEIGHT	HAZARD	DANGER SYMBOL(S)
-----------------	-------------	--------	------------------

No hazardous ingredients

3. HAZARDS IDENTIFICATION**Main hazards and effects:**

None

WITCOVAR 146

4. FIRST AID MEASURES

Swallowing

WHEN MOLTEN ONLY (molten product can cause thermal burns) Obtain medical attention immediately.

Inhalation

No emergency care anticipated.

Skin contact

WHEN MOLTEN ONLY (molten product can cause thermal burns) In serious cases, use emergency shower immediately. Immediately flush skin thoroughly with water for at least 15 minutes while removing contaminated clothing and shoes. Obtain medical attention.

Eye contact

WHEN MOLTEN ONLY (molten product can cause thermal burns) Immediately flush eyes with water and continue washing for at least 15 minutes. Obtain medical attention.

Notes to physician

None

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable : Extinguish with:

- dry chemical
- carbon dioxide (in case of small fires)
- water fog
- foam
- sand or earth

Unsuitable : Do not use water jet.

Special fire fighting procedures

Do not direct a solid stream of water or foam into burning molten material; this may cause spattering and spread the fire.

Special protective equipment for firefighters

Self-contained breathing apparatus.

Unusual fire and explosion hazards

Following products may be produced during a fire: Oxides of carbon.

WITCOVAR 146

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Wear suitable protective equipment.

Environmental precautions

Avoid runoff to sewers or waterways. Dike area of spill to prevent spreading and pump liquid to salvage tank. Allow remaining liquid to solidify, then shovel into containers. Waste: avoid washing into watercourses. Use methods consistent with local regulations or incinerate.

Methods for cleaning up

Dike to contain spill. Take up mechanically. Collect in suitable containers. Stop the leak if it can be done without risk. Clean up with solvent.

7. HANDLING AND STORAGE

HANDLING

Do not handle at temperatures $> +150\text{ }^{\circ}\text{C}$

Ventilation

General (mechanical) room ventilation is expected to be satisfactory for use at room temperature.

STORAGE

Storage requirements

Keep away from heat, sparks and flame. Do not store at temperatures: $> 25\text{ }^{\circ}\text{C}$
Store protected from light

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS

INGREDIENT TYPE	VALUE	REMARK
--------------------	-------	--------

No exposure limits have been established

PERSONAL PROTECTION

Respiratory protection

None expected to be needed.

Hand protection / protective gloves

Personal protectives: WHEN MOLTEN ONLY.
Wear gloves impervious to this material

WITCOVAR 146

Eye protection

Personal protectives: WHEN MOLTEN ONLY.

Safety glasses.

Faceshield

Skin protection

Personal protectives: WHEN MOLTEN ONLY.

Overalls

Other protective equipment

Personal protectives: WHEN MOLTEN ONLY.

Overalls

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state : Solid

Odor : None

Other propertiesMelting point : 60 - 80 °C
Method: ASTM D 127Flash point : > 250 °C
Method: ASTM D92

Autoignition temperature : No data available.

Explosion limits

Upper explosion limits : No data available.

Lower explosion limits : No data available.

Density : 0,80 g/cm³ at 100 °C

Bulk density : No data available.

Vapor pressure : < 0,1 hPa at 20 °C

Vapor density (air=1) : None specified

Evaporation rate (Butyl Acetate=1) : Not applicable

Solubility in water : Negligible

Kinematic viscosity : 6 - 15 mm²/s at 100 °C**Reference No.: 20000000414 - 1.3**

WITCOVAR 146

10. STABILITY AND REACTIVITY

STABILITY

Stable.

Conditions to avoid

Avoid contact with: Strong oxidizing agents.

Incompatible materials

Strong oxidizing agents.

Hazardous combustion products

Combustion may produce the following products:

Carbon monoxide.

Carbon dioxide.

11. TOXICOLOGICAL INFORMATION

GENERAL

No information available.

12. ECOLOGICAL INFORMATION

General

Most hydrocarbon components of these substances will have little or no tendency to partition to air. The half lives for degradation of these hydrocarbons by reaction with hydroxyl radicals, in the troposphere, under the influence of sunlight, will all be less than one day, by extrapolation from the data quoted by Atkinson. Accordingly, any hydrocarbon material which does partition to air will be rapidly photodegraded. (Ref.: Atkinson, R., Gas-phase tropospheric chemistry of organic compounds: a review, Atmos. Environ., vol 24 A, pp. 1-41, 1990)

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations or incinerate.

WITCOVAR 146

14. TRANSPORT INFORMATION

ADR/RID

This product is not regulated by ADR.

IMDG

This product is not regulated by IMDG.

ICAO

This product is not regulated by ICAO.

15. REGULATORY INFORMATION

EC classification

According to EC-regulations this product is not classified or labelled.

Chemical Inventory

Europe : This product is on the EINECS inventory.

16. OTHER INFORMATION

Recommended uses and restrictions

Please consult the product and/or application information bulletins for this product.

A shaded background and a vertical line in the left margin of the report indicate a change compared to the previous version.

WITCOVAR 146

The opinions expressed herein are those of qualified experts within Sonneborn Refined Products B.V.. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and of these opinions and the conditions of use of this product are not within the control of Sonneborn Refined Products B.V., it is the user's obligation to determine the conditions of safe use of the products.