

## Product Data Sheet

# Extra Light Yellow

## Yellow Petroleum Jelly

### Product Description

A fine yellow petroleum jelly, possessing medium fiber and a relatively opaque appearance. Its structure renders it particularly suitable for cold filling into smaller containers. This petroleum jelly meets the requirements of EuP and USP.

t

### Physical Properties

| Properties               | Unit | Method     | Specification    | Typical   |
|--------------------------|------|------------|------------------|-----------|
| Drop melting point       | °C   | ASTM D 127 | 58-65            | 61        |
| Cone penetration at 25°C | dmm  | ASTM D 937 | 160-180          | 164       |
| Congealing point         | °C   | ASTM D 938 | 49-55            | 52        |
| Lovibond colour ½" cell  |      |            | Max.<br>15Y+1.5R | 6.0Y-0.7R |

### Purity

This petroleum jelly meets the purity requirements of the EuP, USP, BP, Ned., Belg.

### Applications

Suitable as a base for ointments, salves, etc. in the pharmaceutical and cosmetic industries, as a rust preventive in the metallurgical industry and in the metal finishing trade. Also in the rubber industry, the manufacture of printing ink, in the textile and rope industries.

Revision date: December 19, 2005

The information presented herein is based on the best data available and is believed to be correct. However, nothing stated in this bulletin is to be taken as a warranty, expressed or implied, regarding the accuracy of the information or the use of our product or products; nor shall anything contained herein be constructed to constitute a permission or recommendation to practice any invention covered by a patent owned by Sonneborn Refined Products B.V., any of its division, or by other, without a license from the owner of the patent