

Snowwhite N

White Petroleum Jelly

Product Description

This is a beautiful, rather firm white petroleum jelly with silky, long-fibred structure and glossy surface. It is odorless and tasteless and stable to light and oxidation. It keeps its good structure during processing. It is highly refined and meets the purity requirements of most internationally known pharmacopoeias, such as EuP, USP, etc.

Physical Properties

| Properties | Unit | Method | Specification | Typical |
|--------------------------|------|------------|---------------|---------|
| Drop melting point | °C | ASTM D 127 | 54-60 | 58 |
| Cone penetration at 25°C | dmm | ASTM D 937 | 160-180 | 168 |
| Congeaing point | °C | ASTM D 938 | 47-53 | 52 |
| Lovibond colour 2" cell | | | Max. 1.5Y | 1.1Y |

Purity

This petroleum jelly meets the purity requirements of the EuP, USP, BP, Belg., Ned., Nord.

Applications

As a result of its ability to bind oil as well as water, this petroleum jelly is mainly utilised for the preparation of unguents, both pigments and emulsion type.

Besides varied use in the cosmetic industry, it finds application as a softener in finishes in the textile trade, imparting to the fabric a fuller feel; also in the foodstuff industry as a lubricant and preservative; in the power cable and condenser industry, metallurgical industry and for hospital use, etc.

Revision date: December 19, 2005

The information presented herein is based on the best data available and is believed to be correct. However, nothing stated in this bulletin is to be taken as a warranty, expressed or implied, regarding the accuracy of the information or the use of our product or products; nor shall anything contained herein be constructed to constitute a permission or recommendation to practice any invention covered by a patent owned by Sonneborn Refined Products B.V., any of its division, or by other, without a license from the owner of the patent