

Specifications for
HYDROBRITE® 200 PO White Mineral Oil

<u>PROPERTIES GUARANTEED</u>	<u>TEST METHOD</u>	<u>LIMITS</u>
Spec. Grav. @ 25°C/25°C	ASTM D4052	0.845/0.885
Visc., Kin. @ 40°C, CST	ASTM D445	39.5/46.0
Acidity	USP (current revision)	PASS
Readily Carbonizable Substances	USP (current revision)	PASS
Solid Paraffin	USP (current revision)	PASS
Limit Of Polycyclic Aromatic Hydrocarbons	USP (current revision)	PASS
Limit Of Sulfur Compounds	USP (current revision)	PASS
Residual Solvents, Reportable Quantity	USP 467	None
Odor	LATM 092	NONE
Color, Saybolt	ASTM D156	30 Min.
Pour Point, °C	ASTM D97	-9 Max.
Refractive Index @ 25°C	ASTM D1218	1.4685/1.4735
GC Distillation, °C, 5%	ASTM D2887	380 Min.

This product is a Mineral Oil USP meeting requirements for USP (current revision) and Food and Drug Administration requirements as per 21 CFR 172.878 and 21 CFR 178.3620(a).

The information contained herein is correct to the best of our knowledge. Your attention is directed to the pertinent Material Safety Data Sheets for the products mentioned herein. All sales are subject to Sonneborn's standard terms and conditions of sale, copies of which are available upon request and which are part of Sonneborn's invoices and/or order acknowledgments. Except as expressly provided in Sonneborn's standard terms and conditions of sale, no warranty, express or implied, including warranty of merchantability or fitness for particular purpose, is made with respect to the products described herein. Nothing contained herein shall constitute permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.