

Specifications for
HYDROBRITE® 550 PO White Mineral Oil

PROPERTIES GUARANTEED	TEST METHOD	LIMITS
Specific Gravity @ 25°C/25°C	ASTM D4052	0.860/0.880
Kin. Viscosity @ 40°C, cSt	ASTM D445	100/125
Acidity	USP (current revision)	PASS
Readily Carbonizable Substances	USP (current revision)	PASS
Solid Paraffin	USP (current revision)	PASS
Limit Of Polycyclic Aromatic Hydrocarbons	USP (current revision)	PASS
Limit Of Sulfur Compounds	USP (current revision)	PASS
Residual Solvents, Reportable Quantity	USP 467	None
Odor	LATM 092	NONE
Color, Saybolt	ASTM D156	30 Min.
Pour Point, °C	ASTM D97	- 9 Max.
Refractive Index @ 25°C	ASTM D1218	1.470/1.478
Paraffinic Carbon, %	ASTM D3238	67.5/72.0
Naphthenic Carbon, %	ASTM D3238	28.0/32.5
Flash Point, COC, °C	ASTM D92	254 Min.
GC Distillation, 5%, °C	ASTM D2887	430 Min.

HYDROBRITE® 550 PO is a Mineral Oil USP meeting requirements for USP (current revision) and FDA requirements as per 21 CFR 172.878 and 21 CFR 178.3620(a).

Supplemental Properties For Hydrobrite® 550 PO White Mineral Oil
Not Guaranteed or Reported on Certificate Of Analysis

Supplemental Properties	Test Method	Typical	EU Limits
D1160 Dist. @ 10 mm Hg ,2.5%, °C	LATM 140	298	N/A
D1160 Dist. @ 10 mm Hg ,5.0%, °C	LATM 140	306	N/A
Kinematic Viscosity @ 100°C, cSt	ASTM D445	12.14	8.5 min.
Average Molecular Weight	ASTM D2502	541	480 min.
Carbon Number at 5% Distillation Point	ASTM D 2887	> 28	25 min.

The information contained herein is correct to the best of our knowledge. Your attention is directed to the pertinent Material Safety Data Sheets for the products mentioned herein. All sales are subject to Sonneborn's standard terms and conditions of sale, copies of which are available upon request and which are part of Sonneborn's invoices and/or order acknowledgments. Except as expressly provided in Sonneborn's standard terms and conditions of sale, no warranty, express or implied, including warranty of merchantability or fitness for particular purpose, is made with respect to the products described herein. Nothing contained herein shall constitute permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.