

Product name: MINERAL JELLY NO 17

---

---

## 1. PRODUCT AND COMPANY IDENTIFICATION

---

Product name: MINERAL JELLY NO 17

Chemical name:

Supplier: Sonneborn, Inc.  
575 Corporate Drive, Suite 415  
Mahwah, NJ 07430 USA

Emergency telephone number: CHEMTREC (24 hours) 800-424-9300  
Sonneborn, Inc. Emergency Response  
(24 hours) 724-756-2210

For MSDS, Product Safety, or regulatory inquiries, call: 877-948-2688

Customer Service: 877-948-2688

---

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

---

COMPONENT	CAS#	CONCENTRATION
-----------	------	---------------

---

---

## 3. HAZARDS IDENTIFICATION

---

### EMERGENCY OVERVIEW

THIS PRODUCT IS A BLEND OF FOOD GRADE PETROLEUM PRODUCTS. IT IS NOT EXPECTED TO PRESENT ANY UNUSUAL HAZARDS, IN PROPER USE.

---

## 4. FIRST AID MEASURES

---

### Swallowing

Do not induce vomiting. Treat symptomatically. Not expected to be toxic by ingestion.

### Skin

No emergency care anticipated. Wash skin with soap and water. Remove contaminated clothing. Wash clothing before re-use. Obtain medical attention if irritation persists.

### Inhalation

Obtain medical attention. Oxygen may be given by qualified personnel if breathing is difficult or cyanosis (blue discoloration of skin) is noted. Give artificial respiration if not breathing. Remove to fresh air if aerosol spray is inhaled. Aspiration may cause pulmonary edema or aspiration pneumonia. Exposed persons should be kept under medical observation for at least 48 hours because delayed effects may occur.

### Eye contact

**Product name: MINERAL JELLY NO 17**

No emergency care anticipated. Flush eyes thoroughly with water for several minutes. Obtain medical attention if discomfort persists.

---

**5. FIRE-FIGHTING MEASURES**

---

<b>Flash point:</b> > 204 °C (400 °F)
---------------------------------------

**NFPA CLASSIFICATION**

Health: 0	Flammability: 1	Reactivity: 0	Special provisions: -
-----------	-----------------	---------------	-----------------------

**Special fire fighting procedures**

Use water spray to cool fire-exposed containers and structures. If a rail or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from the area and let the fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire.

**Special protective equipment for firefighters**

Body covering protective clothing, full "turn-out" gear. Self-contained breathing apparatus with full face-piece operated in positive pressure mode.

**Extinguishing media**

Suitable: Treat as an oil fire.

Small fires:

- CO2
- dry powder
- foam

Large fires:

- alcohol-type foam or universal-type foams
- water fog

Unsuitable: Oil will float on water and can spread any fire.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

**Personal precautions**

Wear protective clothing when taking up spill. Eliminate sources of ignition.

**Environmental precautions**

This product is insoluble in water and will float on the surface. Prevent from entering sewers or drains. Should this product enter sewers or drains, it should be pumped out into an open vessel. Emergency services may need to be called to assist in this operation.

**Methods for cleaning up**

Floor may be slippery; use care to avoid falling.

Small spills Absorb on inert material such as sand, earth, vermiculite.

**Product name: MINERAL JELLY NO 17**

---



---

## 7. HANDLING AND STORAGE

---

### HANDLING

#### Handling precautions

Never use pressure to empty drums. Keep drums tightly closed to prevent contamination. Residual vapors may explode on ignition; do not puncture, drill, grind, or weld near this container. Electrically bond and ground all containers and equipment before transfer or use of material.

### STORAGE

#### Storage requirements

Normal precautions common to safe manufacturing practice should be followed in handling and storage. Store in a dry place. Keep out of strong sunlight. Keep away from heat and flame. Keep container tightly closed.

#### Further information on storage

Keep away from strong oxidizing agents.

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### PERSONAL PROTECTION

#### Respiratory protection

If vapor and/or mist is generated by heating, spraying, etc., wear an organic vapor respirator with a mist filter. No special respiratory protection is normally required.

#### Hand protection / protective gloves

Wear oil resistant gloves.

#### Eye protection

Face shield or chemical splash goggles in case of splashing.

#### Skin protection

Wear protective clothing, such as long sleeves to minimize skin contact.

#### Industrial hygiene measures

Remove contaminated clothing and clean it.

Do not eat or drink at work.

### ENGINEERING CONTROLS

#### Ventilation

Local ventilation is needed in the presence of airborne mists.

### EXPOSURE LIMITS

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Remark</u>
Mineral Oil Mist	TWA (mist), ACGIH	5.0 mg/m <sup>3</sup>	If used in way that generates a "mist" observe the limits for Mineral Oil Mist.

**Product name: MINERAL JELLY NO 17**

STEL (mist), ACGIH

10.0 mg/m<sup>3</sup>

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

**APPEARANCE**

<b>Physical state</b>	Semi-solid    A liquid above the melting point.
<b>Color</b>	White to light yellow
<b>Odor</b>	None

**OTHER PROPERTIES**

<b>Boiling point</b>	No data available.
<b>Melting point</b>	38 - 60 °C at STP unless specified below.
<b>Specific gravity (H<sub>2</sub>O=1)</b>	< 1
<b>Vapor pressure</b>	< 0.005 hPa    (0.00 mmHg)            at 20 °C
<b>Solubility in water</b>	Insoluble
<b>Solubility in organic solvents</b>	Soluble
<b>Partitioning coefficient</b>	log POW: > 6 This product is soluble in oil.
<b>Flash point</b>	> 204 °C    (400 °F) Method: Cleveland open cup ASTM D 92
<b>Percent volatiles</b>	Nil

---

## 10. STABILITY AND REACTIVITY

---

**Stability:** Stable.**Incompatible materials**

Normally unreactive; however avoid contact with:

Strong oxidizing agents.

Sunlight or ultraviolet light.

Heat or high temperature.

**Hazardous combustion products**

Burning can produce the following combustion products:

Oxides of carbon.

Soot

**Product name:** MINERAL JELLY NO 17

---

**Hazardous polymerization:** Will not occur.

---

## 11. TOXICOLOGICAL INFORMATION

---

### SWALLOWING

#### Acute effects

Ingestion is unlikely to have any toxic effects but the product may act as an intestinal lubricant and result in diarrhea and frequent loose stools.

If vomiting occurs, aspiration may cause delayed pulmonary edema and chemical pneumonia.

#### Test results

##### Acute toxicity:

LD50 - Rat

Result: > 5,000 mg/kg

Remark: Test results are based on analogy with a similar material.

### SKIN ABSORPTION

#### Acute effects

Harmful effects are not expected from short periods of contact.

#### Effects of repeated overexposure

Prolonged or repeated contact may lead to skin irritation by dermatitis or oil acne.

### INHALATION

#### Acute effects

Harmful effects are not expected from static vapor at ambient temperature.

Inhalation of mist or spray may be harmful.

#### Chronic effects

Aspiration may cause pulmonary edema or aspiration pneumonia.

Oil deposits in the lung may lead to fibrosis and reduced pulmonary function.

Prolonged or repeated inhalation of excessive amounts of oil mist or vapors may cause irritation of the respiratory tract.

### SKIN CONTACT

#### Acute effects

No evidence of harmful effects from available information.

#### Test results

##### Skin irritation:

Species: Guinea pigs

Result: Non irritating.

### EYE CONTACT

#### Acute effects

No evidence of harmful effects from available information.

#### Test results

##### Eye irritation:

Species: Rabbit

Result: No irritation

### SENSITIZATION

#### Test results:

Species: Skin - Guinea pigs

**Product name: MINERAL JELLY NO 17**

---

Result: Non sensitizing.

---

## 12. ECOLOGICAL INFORMATION

---

This product is stable in water, and can be mechanically separated from water. The water may be suitable for disposal in a biological waste water treatment plant. Not expected to be acutely toxic to aquatic organisms.

---

## 13. DISPOSAL CONSIDERATIONS

---

**General:** Incineration is probably the best means of disposal. Dispose of in accordance with appropriate Federal, State, and local regulations.

---

## 14. TRANSPORT INFORMATION

---

### DOT Classification

This product is not regulated by DOT.

<b>Freight description road:</b> 65 PETROLEUM OIL, N.O.I.B.N
--

### IMDG Classification

This product is not regulated by IMDG.

### ICAO Classification

This product is not regulated by ICAO.

---

## 15. REGULATORY INFORMATION

---

### New Jersey Worker and Community Right-To-Know Act (Labeling Requirements)

Chemical name	CAS#	New Jersey TS Number
Petrolatum Jelly	8009-03-8	
White Mineral Oil	8042-47-5	
Paraffin Wax	63231-60-7	
Microcrystalline Wax	63231-60-7	

**EPA Hazard Categories (SARA 311, 312):** None

### CHEMICAL INVENTORY

Canada: The ingredients of this product are on the DSL.

Europe: The ingredients of this product are on the EINECS inventory.

United States: The ingredients of this product are on the TSCA inventory.

Australia: The ingredients of this product are on the AICS inventory.

**Product name: MINERAL JELLY NO 17**

---

Japan: The ingredients of this product are on the ENCS inventory.

**FDA****Food additive**

This product is a blend of USP grade Petrolatum meeting 21 CFR 172.880, Light Mineral Oil meeting 21 CFR 172.878, and Paraffin wax meeting 21 CFR 172.886. Normally it is used for a variety of cosmetic and medical applications.

---

**16. OTHER INFORMATION**

---

**FURTHER INFORMATION**

MAY BE ON THE INVENTORY LIST BUT NOT NECESSARILY REGISTERED, (Korea, China, New Zealand) CONSULT REGULATORY SPECIALIST.

**HMIS RATING**

Health: 0	Flammability: 1	Reactivity: 0	PPI: -
-----------	-----------------	---------------	--------

**LEGEND**

STP	Standard temperature and pressure
W/W	Weight/Weight
0 (HMIS)	Minimal hazard
1 (HMIS)	Slight hazard
2 (HMIS)	Moderate hazard
3 (HMIS)	Serious hazard
4 (HMIS)	Severe hazard
X (HMIS)	Personal protection rating to be supplied by user depending on use conditions

Copyright 2005 Sonneborn, Inc.

The opinions expressed herein are those of qualified experts within Sonneborn Inc.. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and of these opinions and the conditions of use of this product are not within the control of Sonneborn Inc., it is the user's obligation to determine the conditions of safe use of the products.