

Specifications for
SONOJELL® #9 Petrolatum

<u>PROPERTIES GUARANTEED</u>	<u>TEST METHOD</u>	<u>LIMITS</u>
Melting Point, °C	ASTM D127	41.7/48.9
Melting Point, °F	ASTM D127	107-120
Consistency	ASTM D937	150-170
Lovibond Color, 3" CELL	IP 17	0.5y Max.
Residual Solvents, Reportable Quantity	USP 467	NONE
Odor Rating, Panel Average	LATM 093	0.8 Max.

This product is a blend of Petrolatum USP meeting requirements for USP (current revision) and FDA requirements as per 21 CFR 172.880. Paraffin Wax NF meeting FDA requirements as per 21 CFR 172.876 and Light Mineral Oil NF meeting FDA requirements as per 21 CFR 172.878.

The information contained herein is correct to the best of our knowledge. Your attention is directed to the pertinent Material Safety Data Sheets for the products mentioned herein. All sales are subject to Sonneborn's standard terms and conditions of sale, copies of which are available upon request and which are part of Sonneborn's invoices and/or order acknowledgments. Except as expressly provided in Sonneborn's standard terms and conditions of sale, no warranty, express or implied, including warranty of merchantability or fitness for particular purpose, is made with respect to the products described herein. Nothing contained herein shall constitute permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.