

Specifications for  
**SUNISO® 160 Refrigeration Oil**

<u>PROPERTIES GUARANTEED</u>	<u>TEST METHOD</u>	<u>LIMITS</u>
VISCOSITY @ 40°C, cSt	ASTM D445	29.0/31.0
VISCOSITY INDEX	ASTM D2270	95 Min.
SPECIFIC GRAVITY @ 15°C	ASTM D4052	0.8602/0.8708
FLASH POINT, COC, °C	ASTM D92	204 Min.
POUR POINT, °C	ASTM D97	- 12 Max.
COLOR	ASTM D1500	1.5 Max.
TOTAL ACID NUMBER, mg KOH/g	ASTM D974	1.15 Max.
PHOSPHORUS, PPM	GAM 1031H	485/580

The information contained herein is correct to the best of our knowledge. Your attention is directed to the pertinent Material Safety Data Sheets for the products mentioned herein. All sales are subject to Sonneborn's standard terms and conditions of sale, copies of which are available upon request and which are part of Sonneborn's invoices and/or order acknowledgments. Except as expressly provided in Sonneborn's standard terms and conditions of sale, no warranty, express or implied, including warranty of merchantability or fitness for particular purpose, is made with respect to the products described herein. Nothing contained herein shall constitute permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.