

Specifications for  
**BLANDOL® White Mineral Oil**

<u>PROPERTIES GUARANTEED</u>	<u>TEST METHOD</u>	<u>LIMITS</u>
Specific Gravity @ 25°C/25°C	ASTM D4052	0.839/0.859
Specific Gravity @ 15°C/15°C	ASTM D4052	Report
Kin. Viscosity @ 40°C, mm <sup>2</sup> /s	ASTM D445	14.2/17.0
Acidity	NF (current revision)	PASS
Readily Carbonizable Substances	NF (current revision)	PASS
Solid Paraffin	NF (current revision)	PASS
Limit Of Polycyclic Aromatic Hydrocarbons	NF (current revision)	PASS
Limit Of Sulfur Compounds	NF (current revision)	PASS
Residual Solvents, Reportable Quantity	USP 467	None
Odor	LATM 092	None
Color, Saybolt	ASTM D156	30 Min.
Breakdown Time, Minutes	LATM 017	40 Min.
Infrared Absorption	USP 197F	Pass

This product is a Light Mineral Oil NF meeting requirements for National Formulary (current revision) and Food and Drug Administration requirements as per 21 CFR 172.878 and 21 CFR 178.3620(a).

TYPICAL PROPERTIES FOR BLANDOL® White Mineral Oil

<u>PROPERTIES</u>	<u>TEST METHOD</u>	<u>TYPICAL VALUE</u>
Saybolt Visc. @ 100°F, SUS	ASTM D2161	87