

Specifications for
GLORIA® White Mineral Oil

| <u>PROPERTIES GUARANTEED</u> | <u>TEST METHOD</u> | <u>LIMITS</u> |
|--|------------------------|---------------|
| Specific Gravity @25°C/25°C | ASTM D4052 | 0.859/0.880 |
| Kin. Viscosity @ 40 °C, mm ² /s | ASTM D445 | 39.3/41.5 |
| Say. Viscosity @100 °F, SUS | ASTM D2161 | 205/215 |
| Acidity | USP (current revision) | PASS |
| Readily Carbonizable Substances | USP (current revision) | PASS |
| Solid Paraffin | USP (current revision) | PASS |
| Limit Of Polycyclic Aromatic Hydrocarbons | USP (current revision) | PASS |
| Limit Of Sulfur Compounds | USP (current revision) | PASS |
| Residual Solvents, Reportable Quantity | USP 467 | None |
| Odor | LATM 092 | NONE |
| Color, Saybolt | ASTM D156 | 30 Min. |
| Breakdown Time, Minutes | LATM 017 | 40 Min. |
| Infrared Absorption | USP 197F | PASS |

This product is a Mineral Oil USP meeting requirements of the U.S. Pharmacopeia (current revision) and Food and Drug Administration requirements as per 21 CFR 172.878 and 21 CFR 178.3620A.

The information contained herein is correct to the best of our knowledge. Your attention is directed to the pertinent Material Safety Data Sheets for the products mentioned herein. All sales are subject to Sonneborn's standard terms and conditions of sale, copies of which are available upon request and which are part of Sonneborn's invoices and/or order acknowledgments. Except as expressly provided in Sonneborn's standard terms and conditions of sale, no warranty, express or implied, including warranty of merchantability or fitness for particular purpose, is made with respect to the products described herein. Nothing contained herein shall constitute permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.